

"VK300"





A steam generator with a maximum pressure of 4 bar. The electromechanical controls reflect the tradition of our line "IV".

This compact appliance requires connection to the water mains. The casing is in varnished stainless steel and the lid in varnished aluminium. For its simplicity, sturdiness and power, it is a must in every dental laboratory.

The appliance bears the "CE" and "TÜV-GS" Marks.

Pilot lights

- When lit, the blue light indicates that water in the tank is low and the punp is running.
- When lit, the white light indicates that the heating element is operating.

Gun

- Fitted with safety catch
- Can be positioned on either side, L/R
- Ergonomic
- Special heat-resistant material

Pressure gauge

 To check the pressure in the boiler

Pushbutton

 Used in place of the pedal to control dry steam

Fixed nozzle

 Nozzle for dry steam

VK 300 FFEGIBPEGA Activity The served with the served with

Components

- 3.6 I copper boiler
- Boiler insulated with a fiber resistant to 500° C
- Varnished stainless steel casing
- Varnished aluminium lid
- Copper tubing
- Brass fittings
- Numbered safety valve set at 5.5 bar

Reset push-button

 Cycle reset button, to be used when the pump safety device is triggered.

ON-OFF light switch

Switch for turning the appliance on and off. The green light indicates that the appliance is operating.

Gun control push-buttons

- The left button activates the output of "dry steam".
- The right button activates the output of hot water.
- Both buttons at a time activate the output of a "mixture of water and steam".
- The left button indicates also any thermostat lockout.