

Turbines without a dark side







The instrument range that meets the highest demands. High-end turbines with ultimate technology!



The instrument range for maximum economy.

Proven Synea quality is more accessible than ever before, whatever your budget!

Turbines that meet the highest demands



People have Priority: To make it easier to select one of our new Synea turbines, we listened to your requirements and have now developed two new lines perfectly suited to your needs. Synea Vision: with innovations like the sterilizable Penta LED+ optic ring. And Synea Fusion: a series with top quality and maximum economy.



Light and smoothFatigue-free working with noticeably lighter turbine system.



See better
Best ever contrast and accurate colour reproduction with LED+.



Optimum cooling
The bur tip is continuously cooled in all situations.



Tailor-made turbines
The right head for every application.
With Roto Quick or Multiflex®*
connection.



Best ergonomics

Synea turbines are comfortable in the hand and have a non-slip coating.



ReliabilityTop quality for a long life.

Synea Vision: The dream that has become reality



Ultimate high-end technology for excellent preparation results: Discover the Synea Vision range with unique innovations such as the shadow-free Penta LED+ optic ring or the special new scratch-resistant surface coating!



Tailor-made instruments
Like the TA-94 microturbine for minimally invasive applications.



Scratch-resistant surface
A special scratch-resistant coating keeps it looking immaculate, and helps maintain its value.



Revolutionary
Penta LED+: the only sterilizable
5x LED ring in the world.



No shadows
Penta LED+: for the first time ever,
shadow-free illumination at the
treatment site!



Synea Vision: Technical data

Types with integrated



TK-94 L / TK-94 LM**

1.5 mm

16 mm

39 g / 67 g

 3 ± 0 ,3 bar

2,5 to 4 bar

5x

59 dB (A)



TK-97 L / TK-97 LM**

2 mm

21 mm

38 g / 68 g

 3 ± 0 ,3 bar

2,5 to 4 bar

5x

57 dB (A)



TK-98 L / TK-98 LM**

2 mm

25 mm

40 g/69 g

 3 ± 0 ,3 bar

2,5 to 4 bar

5x

57 dB (A)



TK-100 L / TK-100 LM**

2.5 mm

 $25\,mm$

40 g / 70 g

 $3\pm0,3$ bar

2,5 to 4 bar

5x

57 dB (A)

ceramic ball bearings:	TROTE/TROTEM	THOSE EXTENSION EN	TROOL/ TROOLIN	11(100 E) 11(100 E)
Light:	LED+ / compact glass rod	Penta LED+ / compact glass rod	Penta LED+ / compact glass rod	Penta LED+ / compact glass rod
CRI (LED version):	> 90	> 90	> 90	> 90
Colour temperature: (LED version):	5,500 K	5,500 K	5,500 K	5,500 K
Luminous flux (lumens):	6.0 / 4.0*	6.0 / 4.0*	6.0 / 4.0*	6.0 / 4.0*
Illuminating power:	25,000 lux	25,000 lux	25,000 lux	25,000 lux
Coupling:	1 Roto Quick2 Multiflex®**	Roto Quick Multiflex®**	Roto Quick Multiflex®**	1 Roto Quick 2 Multiflex®**
Head size:	0 9 mm	0 10 mm	0 11,5 mm	0 13 mm
Head height:	17.2 mm (with bur 16 mm)	21.1 mm (with bur 19 mm)	21.4 mm (with bur 19 mm)	21.4 mm (with bur 19 mm)
Power:	12 W	18 W	21 W	22 W
rpm (min ⁻¹):	430,000	400,000	360,000	330,000
Rotary instruments:	FG bur, as per EN ISO 1797-1:1995, with 0 1,6 mm			

The power and rotary speeds of air drives depend greatly on the quality of the turbine hoses used and may therefore vary from the specified values.

^{**} Multiflex® is a registered trademark of Kaltenbach & Voigt GmbH, Germany



Max. operating part diameter:

Roto Quick connection

operating pressure: Multiflex® connection

operating pressure:
Spray outlets:

Max. length:

Weight:

Volume:

W&H Roto Quick couplings enable the versatile use of instruments with LED+, LED and halogen light

- > Click and nul
- > Continuous regulation of the spray water supply
- > Clean head system
- > Sterilizabl
- > 24-month guarantee



W&H RM-34 LED coupling for Multiflex®** connection

- > Use of LED without requiring changes to an optic dental unit
- > Long LED service life
- Continuous regulation of the spray water supply
- > Clean head system
- > 24-month guarantee

^{*} Values apply for use of RM-34 LED with DC power supply

Synea Fusion: Synea turbines with maximum efficiency



Uncompromising user comfort combined with outstanding economy:

Discover the benefits of the Synea Fusion line!

Your advantages at a glance

- > Small head
- > Thermo washer disinfectable up to 135°C
- > Long service life
- > Short service times
- > Lightweight and quiet



Experience LED+
Optimum illumination, natural colour reproduction and LED positioned directly beneath the instrument head.



Optimum cooling of four sides
Continuous cooling with
Quattro Spray.



Synea Fusion: Technical data







Types:	TG-98 L / TG-98 LM** / TG-98	TG-97 L / TG-97 LM** / TG-97	
Light:	LED +/ compact glass rod / –	LED + / compact glass rod / –	
CRI (LED version):	> 90	> 90	
Colour temperature (LED version):	5,500 K*	5,500 K	
Luminous flux (lumens):	6.0 / 4.0* / –	6.0 / 4.0*/-	
Illuminating power:	25,000 Lux	25,000 Lux	
Coupling:	1 Roto Quick 2 Multiflex®**	• Roto Quick • Multiflex®**	
Head size:	0 11.5 mm	0 10 mm	
Head height:	21.4 mm (with bur 19 mm)	21.1 mm (with bur 19 mm)	
Power:	19 W	16 W	
rpm (min ⁻¹):	360,000	390,000	
Rotary instruments:	FG bur, as per EN ISO 1797-1:1995, with 0 1,6 mm		
Max. operating part diameter:	2 mm 2 mm		
Max. length:	25 mm	21 mm	
Weight:	42 g/70 g/42 g	40 g/68 g/40 g	
Roto Quick connection operating pressure: Multiflex® connection operating pressure:	$3\pm0,3$ bar 2.5 to 4 bar	$3\pm0,3$ bar 2.5 to 4 bar	
Spray outlets:	4x	4x	
Volume:	59 dB (A)	59 dB (A)	

The power and rotary speeds of air drives depend greatly on the quality of the turbine hoses used and may therefore vary from the specified values.

^{**} Multiflex® is a registered trademark of Kaltenbach & Voigt GmbH, Germany



W&H Roto Quick couplings enable the versatile use of instruments with LED+, LED and halogen light

- > Click and pu
- > Continuous regulation of the spray water supply
- > Clean head system
- > Sterilizabl
- > 24-month guarantee



W&H RM-34 LED coupling for Multiflex®** connection

- > Use of LED without requiring changes to an optic dental unit
- > Long LED service life
- Continuous regulation of the spray water supply
- > Clean head system
- > 24-month guarantee

 $^{^{*}}$ Values apply for use of RM-34 LED with DC power supply



Bring Synea Vision to life!

Download the »W&H AR« App to your smartphone or tablet PC free of charge from Google Play (for Android) or the Apple App Store. Open the App and hold your device 50 cm from the picture.

W&H Dentalwerk Bürmoos GmbH Ignaz-Glaser-Straße 53, Postfach 1 5111 Bürmoos, Austria t + 43 6274 6236-0 f + 43 6274 6236-55 office@wh.com

wh.com